



Korean Solaris Release Overview

Sun Microsystems, Inc.
4150 Network Circle
Santa Clara, CA 95054
U.S.A.

Part No: 816-0683-10
May 2002

Copyright 2002 Sun Microsystems, Inc. 4150 Network Circle, Santa Clara, CA 95054 U.S.A. All rights reserved.

This product or document is protected by copyright and distributed under licenses restricting its use, copying, distribution, and decompilation. No part of this product or document may be reproduced in any form by any means without prior written authorization of Sun and its licensors, if any. Third-party software, including font technology, is copyrighted and licensed from Sun suppliers.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California. UNIX is a registered trademark in the U.S. and other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, the Sun logo, docs.sun.com, AnswerBook, AnswerBook2, and Solaris are trademarks, registered trademarks, or service marks of Sun Microsystems, Inc. in the U.S. and other countries. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the U.S. and other countries. Products bearing SPARC trademarks are based upon an architecture developed by Sun Microsystems, Inc.

The OPEN LOOK and Sun™ Graphical User Interface was developed by Sun Microsystems, Inc. for its users and licensees. Sun acknowledges the pioneering efforts of Xerox in researching and developing the concept of visual or graphical user interfaces for the computer industry. Sun holds a non-exclusive license from Xerox to the Xerox Graphical User Interface, which license also covers Sun's licensees who implement OPEN LOOK GUIs and otherwise comply with Sun's written license agreements.

Federal Acquisitions: Commercial Software—Government Users Subject to Standard License Terms and Conditions.

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

Copyright 2002 Sun Microsystems, Inc. 4150 Network Circle, Santa Clara, CA 95054 U.S.A. Tous droits réservés

Ce produit ou document est protégé par un copyright et distribué avec des licences qui en restreignent l'utilisation, la copie, la distribution, et la décompilation. Aucune partie de ce produit ou document ne peut être reproduite sous aucune forme, par quelque moyen que ce soit, sans l'autorisation préalable et écrite de Sun et de ses bailleurs de licence, s'il y en a. Le logiciel détenu par des tiers, et qui comprend la technologie relative aux polices de caractères, est protégé par un copyright et licencié par des fournisseurs de Sun.

Des parties de ce produit pourront être dérivées du système Berkeley BSD licenciés par l'Université de Californie. UNIX est une marque déposée aux Etats-Unis et dans d'autres pays et licenciée exclusivement par X/Open Company, Ltd.

Sun, Sun Microsystems, le logo Sun, docs.sun.com, AnswerBook, AnswerBook2, et Solaris sont des marques de fabrique ou des marques déposées, ou marques de service, de Sun Microsystems, Inc. aux Etats-Unis et dans d'autres pays. Toutes les marques SPARC sont utilisées sous licence et sont des marques de fabrique ou des marques déposées de SPARC International, Inc. aux Etats-Unis et dans d'autres pays. Les produits portant les marques SPARC sont basés sur une architecture développée par Sun Microsystems, Inc.

L'interface d'utilisation graphique OPEN LOOK et Sun™ a été développée par Sun Microsystems, Inc. pour ses utilisateurs et licenciés. Sun reconnaît les efforts de pionniers de Xerox pour la recherche et le développement du concept des interfaces d'utilisation visuelle ou graphique pour l'industrie de l'informatique. Sun détient une licence non exclusive de Xerox sur l'interface d'utilisation graphique Xerox, cette licence couvrant également les licenciés de Sun qui mettent en place l'interface d'utilisation graphique OPEN LOOK et qui en outre se conforment aux licences écrites de Sun.

CETTE PUBLICATION EST FOURNIE "EN L'ETAT" ET AUCUNE GARANTIE, EXPRESSE OU IMPLICITE, N'EST ACCORDEE, Y COMPRIS DES GARANTIES CONCERNANT LA VALEUR MARCHANDE, L'APTITUDE DE LA PUBLICATION A REpondre A UNE UTILISATION PARTICULIERE, OU LE FAIT QU'ELLE NE SOIT PAS CONTREFAISANTE DE PRODUIT DE TIERS. CE DENI DE GARANTIE NE S'APPLIQUERAIT PAS, DANS LA MESURE OU IL SERAIT TENU JURIDIQUEMENT NUL ET NON AVENU.



020111@3062



Contents

Preface 5

Overview of Features 9

New Localized Features 9

Language Support 10

 Locales 10

 Locale Categories 11

Common Desktop Environment (CDE) 12

Printing Facilities 12

Remote User Facilities 13

Developer Facilities 14

 Messaging Facilities 14

Preface

Korean Solaris Release Overview is an overview of information specific to the Korean Solaris™ 9 operating environment.

About This Book

This document is for someone who wants a brief overview of the localized product features of the Korean Solaris operating environment. It introduces new features and basic terms that describe the Korean Solaris 9 localization.

Related Books

For the most up-to-date information about the release, see the document that relates to your hardware platform:

- *Solaris 9 (SPARC Platform Edition) Release Notes*

For general users:

- *Korean Solaris User's Guide*
- *Solaris Common Desktop Environment: User's Guide*

For system administrators and advanced users:

- *Korean Solaris System Administrator's Guide*
- *Solaris Common Desktop Environment: Advanced User's and System Administrator's Guide*

For developers/programmers and advanced users:

- *International Language Environments Guide*

Accessing Sun Documentation Online

The docs.sun.comSM Web site enables you to access Sun technical documentation online. You can browse the docs.sun.com archive or search for a specific book title or subject. The URL is `http://docs.sun.com`.

Typographic Conventions

The following table describes the typographic changes used in this book.

TABLE P-1 Typographic Conventions

Typeface or Symbol	Meaning	Example
AaBbCc123	The names of commands, files, and directories; on-screen computer output	Edit your <code>.login</code> file. Use <code>ls -a</code> to list all files. <code>machine_name% you have mail.</code>
AaBbCc123	What you type, contrasted with on-screen computer output	<code>machine_name% su</code> Password:
<i>AaBbCc123</i>	Command-line placeholder: replace with a real name or value	To delete a file, type <code>rm filename</code> .
<i>AaBbCc123</i>	Book titles, new words, or terms, or words to be emphasized.	Read Chapter 6 in <i>User's Guide</i> . These are called <i>class</i> options. You must be <i>root</i> to do this.

Shell Prompts in Command Examples

The following table shows the default system prompt and superuser prompt for the C shell, Bourne shell, and Korn shell.

TABLE P-2 Shell Prompts

Shell	Prompt
C shell prompt	machine_name%
C shell superuser prompt	machine_name#
Bourne shell and Korn shell prompt	\$
Bourne shell and Korn shell superuser prompt	#

Overview of Features

The Korean Solaris™ 9 operating environment is the internationalization and Korean localization of the Solaris operating environment and the Common Desktop Environment (CDE) window system.

The following sections provide information on the facilities you can use to input, display, and print multibyte Korean characters in the Solaris 9 operating environment.

- “New Localized Features” on page 9
- “Language Support” on page 10
- “Common Desktop Environment (CDE)” on page 12
- “Printing Facilities” on page 12
- “Remote User Facilities” on page 13
- “Developer Facilities” on page 14

New Localized Features

The following new collation locales provide you dictionary collation for all Korean Hangul and Hanja characters supported in each locale.”

- ko_KR.EUC@dict
- ko_KR.UTF-8@dict

Language Support

The Solaris 9 operating environment builds inherent internationalization features into every localized product. Localization facilities support the ANSI C recommendations for internationalization and localization that define the locale and related categories.

Locales

A *locale* contains the language with culturally specific information and conventions for a particular global region. Each process in the Solaris operating environment has the following set of locale attributes:

- Locale settings, which provide the `locale` and `setlocale` commands you use to list and set attributes before you start a process from the command line.
For example, the Korean locales and the English/ASCII locale both have a category that defines the display of time and date according to the cultural format, as well as the actual Korean or English/ASCII characters for time and date.
- Codesets, which support coding conventions for the KS X 1001 and KS X 1005-1 character sets that enable you to input and, display, and print Korean text in file names, system messages, and terminal (TTY), email, and data file content.
- `htt` input method server, which handles Korean input for the Solaris operating environment. The `htt` server, which receives your keyboard input and converts it to Korean characters that are used in Korean Solaris applications.

Korean Locales

The Korean Solaris operating environment provides simultaneous support for the locales listed in the following table. The locales look the same to the end user, but the internal character encoding is different.

TABLE 1-1 Korean Locales

Locale	Description
<code>ko_KR.EUC (ko)</code>	Korean EUC (KS X)
<code>ko_KR.UTF-8 (ko.UTF-8)</code>	Korean UTF-8 (Unicode 3.1)

Korean Codesets

The following table lists the supported codesets for each Korean locale.

TABLE 1-2 Korean Codesets

Locale	Codeset
ko_KR.EUC (ko)	KS X 1001
ko_KR.UTF-8 (ko.UTF-8)	UTF-8

Korean Input Methods and Fonts

The Korean Solaris 9 operating environment provides input methods and fonts for all characters covered the ISO-10646 standard. These methods and fonts allow you to input and output any character in any language.

The following input methods are supported for the ko_KR.EUC (ko) and the ko_KR.UTF-8 (ko.UTF-8) locales:

- Hangul 2-BeolSik (one set of consonants and one set of vowels)
- Hangul-Hanja conversion
- Special character
- Hexadecimal code

For a complete list of scalable and bitmap fonts supported for the ko_KR.EUC (ko) and the ko_KR.UTF-8 (ko.UTF-8) locales, see the *International Language Environments Guide*.

Note – You can use Hangul or standard Sun keyboards to enter Korean text.

Locale Categories

In the Korean Solaris 9 operating environment, you can use the following general and specific categories as defined by ANSI C for the Korean and English locales.

- General LC_ALL setting that invokes all of the categories for locale-related aspects of the environment.
- Specific settings for particular aspects of the environment, which include:
 - LC_CTYPE
 - LC_TIME
 - LC_NUMERIC
 - LC_MONETARY
 - LC_COLLATE
 - LC_MESSAGES

For example, the Korean and the English/ASCII locales have the LC_TIME category that defines the display of the time and date according to the cultural format, as well as the actual Korean or English/ASCII characters used in the display.

Common Desktop Environment (CDE)

CDE is an internationalized graphical user environment with a rich set of desktop applications. The environment has been localized for Korean and other languages. You can work with two or more localized applications simultaneously on the same desktop. Localized CDE applications include the following:

- File Manager, which is a graphical user interface you can use to access files and directories.
- Mailer, which is an application you use to send, receive, and manage email messages. You can drag-and-drop messages and files between the Mailer and other applications.
- Print Manager, which is a graphical front end to the print command that supports drag-and-drop file transfer operations.
- Text editor, which is available in CDE tools such as the Mailer composition window. This application allows you to enter Korean and English characters in the same document.
- Calendar Manager, which helps you manage business and social appointments. You can to send automatic reminders from the calender through the Mailer application.
- Personal Digital Assistant (PDA) Synchronization, which enables you to synchronize data from CDE applications, such as Calendar Manager, with data in similar applications on your PDA. PDA synchronization also enables you to install applications and databases from a workstation or server to a PDA.

Note – The OpenWindows™ environment is no longer supported for use in this release.

Printing Facilities

The Solaris environment provides the following support for Korean printing:

- A line printer with built-in fonts that enables you to use `lp` and `iconv` utilities to print any text file encoded in `wansung`, `johab`, `unicode`, for example. Your system administrator can also set up print filters to automatically convert input from EUC to the codeset of the targeted printer.
- Postscript-based line printer emulation that provides the `xetops` and `xutops` utilities that convert Korean text to bit-mapped images for printing. These utilities enable you to print Korean characters using a Postscript-based printer that does

not have Korean fonts loaded. Some applications generate Postscript files with embedded Korean fonts. For example, you can print Postscript CID fonts to any Postscript level 3 printer without modification to the operating system.

The `mp` program reads each filename in sequence and generates a graphical representation of the content in PostScript format. The program accepts international text files of various Solaris locales and produces output which is appropriate for the specified locale. The output can contain proper text layout, bidirectional text rendering, and character shaping. Depending on each locale's system font configuration for `mp`, the PostScript output file can contain glyph images from Solaris system-resident scalable or bitmap fonts.

- Complex text layout (CTL) is supported in `mp`. For more information about Complex Text Layout, see the chapter “Complex Text Layout” in *International Language Environments Guide*.
- An `Xprt` facility that enables developers of X-windows applications to create device-independent print jobs.
- A font downloader command, `fdl`, that enables you to install and remove supported fonts from Postscript printers. The supported font types include: Postscript Types 1, 9 (CID Type 0), 10 (CID type 1), 11 (CID type 2), CMap files, and TrueType.

Remote User Facilities

The following list summarizes the Korean Solaris 9 remote user facilities:

- Terminals that use Combination code (KSC 5601-1992) and Completion code (KSC 5601). The terminals must have a method to input Korean characters, that is, to run Hangul input conversion.

For information on using different types of terminals, refer to the *Korean Solaris System Administrator's Guide* and the *International Language Environments Guide*

- Telnet emulators that support input methods and fonts used on non-Sun equipment that supports Korean characters. Emulators enable the display of Korean terminal sessions, including certain versions of Korean Windows.
- SunRay™ enterprise server software running on the Solaris operating environment that supports SunRay enterprise appliances. With the locales installed on the server, SunRay appliances are able to support localized X applications, including the CDE desktop tools.
- X11 remote hosts that allow you to run localized applications in the Solaris environment on a remote host. When you connect to the remote host and set the locale before login, you can use the local host to display localized applications with the aid of locale fonts and related input methods.

Developer Facilities

You can add a new locale or variations of existing locales to the Solaris 9 internationalized software environment. If you are a developer responsible for building locales, consult the *International Language Environments Guide* for additional information.

Messaging Facilities

The Solaris 9 messaging facilities provide localized versions of messages available for a locale. You can add localized messages without recompiling an internationalized application. Messages that are localized use facilities such as the following:

- OS messages that use facilities that conform to XPG4 and POSIX specifications.
- CDE messages that use CDE resource files.
- Java™ message localization that is implemented with Java resource bundles.