

Oracle® Database

Quick Installation Guide

10g Release 1 (10.1.0.3) for Solaris Operating System (x86)

Part No. B13972-01

September 2004

ORACLE®

Copyright © 1996, 2004, Oracle. All rights reserved.

The Programs (which include both the software and documentation) contain proprietary information; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs, except to the extent required to obtain interoperability with other independently created software or as specified by law, is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. This document is not warranted to be error-free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose.

If the Programs are delivered to the United States Government or anyone licensing or using the Programs on behalf of the United States Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the Programs, including documentation and technical data, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement, and, to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software--Restricted Rights (June 1987). Oracle Corporation, 500 Oracle Parkway, Redwood City, CA 94065

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee's responsibility to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and we disclaim liability for any damages caused by such use of the Programs.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

The Programs may provide links to Web sites and access to content, products, and services from third parties. Oracle is not responsible for the availability of, or any content provided on, third-party Web sites. You bear all risks associated with the use of such content. If you choose to purchase any products or services from a third party, the relationship is directly between you and the third party. Oracle is not responsible for: (a) the quality of third-party products or services; or (b) fulfilling any of the terms of the agreement with the third party, including delivery of products or services and warranty obligations related to purchased products or services. Oracle is not responsible for any loss or damage of any sort that you may incur from dealing with any third party.

This guide describes how to quickly install Oracle Database 10g on Solaris x86 systems. It includes information about the following:

1. [Documentation Accessibility](#)
2. [Review Information About this Guide](#)
3. [Log In to the System as root](#)
4. [Check the Hardware Requirements](#)
5. [Check the Software Requirements](#)
6. [Create Required UNIX Groups and User](#)
7. [Create Required Directories](#)
8. [Configure Kernel Parameters](#)
9. [Mount the Product Disc](#)
10. [Log In as the oracle User and Configure the oracle User's Environment](#)
11. [Install Oracle Database 10g](#)
12. [Install Products from the Oracle Database 10g Companion CD](#)
13. [What to Do Next](#)

14. Additional Information

1 Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible, with good usability, to the disabled community. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For additional information, visit the Oracle Accessibility Program Web site at

<http://www.oracle.com/accessibility/>

Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

2 Review Information About this Guide

This guide describes how to install Oracle Database 10g using the default installation options.

Tasks Described in this Guide

The procedures in this guide describe how to:

- Configure your system to support Oracle Database 10g
- Install the Oracle Database 10g software on a local file system
- Configure a general-purpose Oracle database that uses the local file system for database file storage
- Install software from the Oracle Database 10g Companion CD which improves the performance of Oracle Database 10g on your system

Results of a Successful Installation

After you successfully install Oracle Database 10g:

- The database that you created and the default Oracle Net listener process are running on the system
- Oracle Enterprise Manager Database Control and *iSQL*Plus* are running and can be accessed using a Web browser

- A single-node version of the Oracle Cluster Synchronization Services (CSS) daemon is running and is configured to start automatically when your system boots

Tasks Not Described in this Guide

This guide does **not** describe how to complete the following tasks:

- Installing the software on a system that has an existing Oracle software installation
- Installing Oracle Cluster Ready Services (CRS) and Oracle Real Application Clusters (RAC) on a cluster
- Enabling Enterprise Manager e-mail notifications or automated backups
- Using alternative storage options such as Automatic Storage Management (ASM) or raw devices for database storage

Where to Get Additional Installation Information

For more detailed information about installing Oracle Database 10g, including information about the tasks not described in this guide, see one of the following guides:

- If you are installing the software on a single system, see the *Oracle Database Installation Guide for UNIX Systems*.

- If you are installing Oracle Real Application Clusters, see the *Oracle Real Application Clusters Installation and Configuration Guide*

This guide also describes how to install Oracle Cluster Ready Services, which is a prerequisite for RAC installations.

Both of these guides are available on the product disc. To access them, use a Web browser to open the `welcome.htm` file, either in the top-level directory of the CD-ROM or in the `db` directory on the DVD-ROM, then select the **Documentation** tab.

3 Log In to the System as root

Before you install the Oracle software, you must complete several tasks as the `root` user. To log in as the `root` user, complete one of the following procedures:

Note: You must install the software from an X window workstation, an X terminal, or a PC or other system with X server software installed.

- If you are installing the software from an X Window System workstation or X terminal:

1. Start a local terminal session, for example, an X terminal (`xterm`).
2. If you are not installing the software on the local system, enter the following command to enable remote hosts to display X applications on the local X server:

```
$ xhost +
```

3. If you are not installing the software on the local system, use the `ssh`, `rlogin`, or `telnet` command to connect to the system where you want to install the software:

```
$ telnet remote_host
```

4. If you are not logged in as the `root` user, enter the following command to switch user to `root`:

```
$ su - root
password:
#
```


- If you are installing the software from a PC or other system with X server software installed:

Note: If necessary, see your X server documentation for more information about completing this procedure. Depending on the X server software that you are using, you may need to complete the tasks in a different order.

1. Start the X server software.
2. Configure the security settings of the X server software to permit remote hosts to display X applications on the local system.
3. Connect to the remote system where you want to install the software and start a terminal session on that system, for example, an X terminal (`xterm`).
4. If you are not logged in as the `root` user on the remote system, enter the following command to switch user to `root`:

```
$ su - root
password:
```

4 Check the Hardware Requirements

The system must meet the following minimum hardware requirements:

Requirement	Minimum Value
Physical memory (RAM)	512 MB (524288 KB)
Swap space	1 GB (1048576 KB) or twice the size of RAM On systems with 2 GB or more of RAM, the swap space can be between one and two times the size of RAM
Disk space in /tmp	400 MB (409600 KB)
Disk space for software files	2.5 GB (2621440 KB) This value includes 1 GB (1048576 KB) of disk space required to install the Oracle Database 10g Products from the Companion CD (optional, but recommended).
Disk space for database files	1.2 GB (1258290 KB)

To ensure that the system meets these requirements, follow these steps:

1. To determine the physical RAM size, enter the following command:

```
# /usr/sbin/prtconf | grep "Memory size"
```

If the size of the physical RAM installed in the system is less than 512 MB, you must install more memory before continuing.

2. To determine the size of the configured swap space, enter the following command:

```
# /usr/sbin/swap -s
```

If necessary, see your operating system documentation for information about how to configure additional swap space.

3. To determine the amount of free disk space available in the `/tmp` directory, enter the following command:

```
# df -h /tmp
```

If there is less than 400 MB of disk space available in the `/tmp` directory, complete one of the following steps:

- Delete unnecessary files from the `/tmp` directory to achieve the required disk space.
 - Set the `TEMP` and `TMPDIR` environment variables when setting the `oracle` user's environment (described later).
 - Extend the file system that contains the `/tmp` directory. If necessary, contact your system administrator for information about extending file systems.
4. To determine the amount of free disk space available on the system, enter the following command:

```
# df -h
```

This command displays the disk space usage on all mounted file systems. To complete the installation, the system must satisfy *either* of the following conditions:

- 3.7 GB (3879731 KB) of free disk space is available on two file systems: one with at least 2.5 GB (2621440 KB) free for the Oracle software and another with at least 1.2 GB free for the preconfigured database

- 3.7 GB of free disk space is available for the Oracle software and database on a single file system

Note: While installing the Oracle database on a disk drive separate from the software does provide a performance improvement, for best performance, the Oracle database files should be distributed across three or more disks. The *Oracle Database Installation Guide for UNIX Systems* describes this more complex and time-consuming type of installation. However, this type of installation is recommended only for experienced users.

5 Check the Software Requirements

The system must meet the following minimum software requirements:

- The version of Solaris must be Solaris 9.
- The following packages must be installed:

SUNWarc	SUNWlibms	SUNWilof
SUNWbtool	SUNWspot	SUNWilcs
SUNWhea	SUNWi15cs	SUNWlibm
SUNWtoo	SUNWxwfont	

- The following patches (or later versions) must be installed:
 - 111713-06, SunOS 5.9_x86: Shared library patch for C++
 - 111728-03, SunOS 5.9_x86: Math Library (libm) patch
 - 112234-12, SunOS 5.9_x86: Kernel Patch
 - 113986-08, SunOS 5.9_x86: linker Patch
 - 115114-02, SunOS 5.9_x86: Patch for assembler
 - 116013-02, SunOS 5.9_x86: ps utility patch
(Available only from your local Sun solution center)

To ensure that the system meets these requirements, follow these steps:

1. To determine which version of Solaris is installed, enter the following command:

```
# uname -r  
5.9
```

In this example, the version shown is Solaris 9 (5.9). If necessary, see your operating system documentation for information about upgrading the operating system.

2. To determine whether the required packages are installed, enter a command similar to the following:

```
# pkginfo -i SUNWarc SUNWbtool SUNwhea SUNWlibm \  
SUNWlibms SUNWsprot SUNWtoo SUNWilof \  
SUNWilcs SUNWi15cs SUNWxfnt
```

If a package is not installed, then install it. See your operating system or software documentation for information about installing packages.

3. To determine whether an operating system patch is installed, enter a command similar to the following:

```
# /usr/sbin/patchadd -p | grep patch_number
```

If an operating system patch is not installed, download it from the following Web site and install it:

<http://sunsolve.sun.com>

6 Create Required UNIX Groups and User

The following local UNIX groups and user must exist on the system:

- The `oinstall` group (the Oracle Inventory group)
- The `dba` group (the OSDBA group)
- The `oracle` user (the Oracle software owner)

The `oinstall` and `dba` groups and the `oracle` user may already exist on your system. To determine whether they exist already, and if necessary, to create them, follow these steps:

1. To determine whether the `oinstall` and `dba` groups exist, enter the following commands:

```
# grep oinstall /etc/group
# grep dba /etc/group
```

If the output from these commands shows the specified group name, that group already exists.

2. If necessary, enter the following commands to create the `oinstall` and `dba` groups:

```
# /usr/sbin/groupadd oinstall
# /usr/sbin/groupadd dba
```

3. To determine whether the `oracle` user exists and belongs to the correct groups, enter the following command:

```
# id -a oracle
```

If the `oracle` user exists, this command displays information about the groups to which the user belongs. The output should be similar to the following, indicating that `oinstall` is the primary group and `dba` is a secondary group:

```
uid=502(oracle) gid=502(oinstall) groups=502(oinstall),503(dba)
```

4. If necessary, complete one of the following actions:

- If the `oracle` user exists, but its primary group is not `oinstall` or it is not a member of the `dba` group, enter the following command:

```
# /usr/sbin/usermod -g oinstall -G dba oracle
```

- If the `oracle` user does not exist, enter the following command to create it:

```
# /usr/sbin/useradd -g oinstall -G dba oracle
```

This command creates the `oracle` user and specifies `oinstall` as the primary group and `dba` as the secondary group.

5. Enter the following command to set the password of the `oracle` user:

```
# passwd oracle
```

7 Create Required Directories

Create directories with names similar to the following and specify the correct owner, group, and permissions for them:

- `/u01/app/oracle` (the Oracle base directory)
- `/u02/oradata` (an optional Oracle datafile directory)

The Oracle base directory must have 2.5 GB (2621440 KB) of free disk space, or 3.7 GB (3879731 KB) of free disk space if you choose not to create a separate Oracle datafile directory. The Oracle datafile directory must have 1.2 GB of free disk space.

Note: If you do not want to create a separate Oracle datafile directory, you can install the datafiles in a subdirectory of the Oracle base directory (not recommended for production databases).

To determine where to create these directories, follow these steps:

1. Enter the following command to display information about all mounted file systems:

```
# df -h
```

This command displays information about all of the file systems mounted on the system, including:

- The physical device name
 - The total amount, used amount, and available amount of disk space, in kilobytes
 - The mount point directory for that file system
2. From the display, identify either one or two file systems that meet the following requirements:
- Two file systems:
Identify one file system with 2.5 GB of free disk space, for the Oracle base directory, and another file system with 1.2 GB of free disk space for the Oracle datafile directory.
 - One file system:
Identify one file system with 3.7 GB of free disk space, for both the Oracle base directory and the Oracle datafile directory.
3. Note the name of the mount point directory for each file system that you identified.

In the following examples, /u01 is the mount point directory used for the software and /u02 is the mount point directory used for the Oracle datafile directory. You must specify the appropriate mount point directories for the file systems on your system.

To create the required directories and specify the correct owner, group, and permissions for them, follow these steps:

Note: In the following procedure, replace /u01 and /u02 with the appropriate mount point directories that you identified in Step 3 previously.

1. Enter the following command to create subdirectories in the mount point directory that you identified for the Oracle base directory:

```
# mkdir -p /u01/app/oracle
```

2. If you intend to use a second file system for the Oracle database files, create an `oradata` subdirectory in the mount

point directory that you identified for the Oracle datafile directory (shown as /u02 in the examples):

```
# mkdir /u02/oradata
```

3. Change the owner and group of the directories that you created to the `oracle` user and the `oinstall` group:

```
# chown -R oracle:oinstall /u01/app/oracle
# chown -R oracle:oinstall /u02/oradata
```

4. Change the permissions on the directories that you created to `775`:

```
# chmod -R 775 /u01/app/oracle
# chmod -R 775 /u02/oradata
```

8 Configure Kernel Parameters

Verify that the following kernel parameters are set to values greater than or equal to the recommended value shown:

Parameter	Recommended Value
semsys:seminfo_semmni	100
semsys:seminfo_semmns	1024
semsys:seminfo_semmsl	256
semsys:seminfo_semvmx	32767
shmsys:shminfo_shmmax	4294967295
shmsys:shminfo_shmmni	100

To view the current value specified for these kernel parameters, and to change them if necessary, follow these steps:

1. To view the current values of these parameters, enter the following commands:

```
# /usr/sbin/sysdef | grep SEM
# /usr/sbin/sysdef | grep SHM
```

2. If you must change any of the current values, follow these steps:

- a. Create a backup copy of the `/etc/system` file, for example:

```
# cp /etc/system /etc/system.orig
```

- b. Open the `/etc/system` file in any text editor:

```
# vi /etc/system
```

- c. To specify new values for the parameters, add lines similar to the following to the `/etc/system` file, or edit the lines if the file already contains them:

```
set semsys:seminfo_semgni=100
set semsys:seminfo_semns=1024
set semsys:seminfo_semmsl=256
set semsys:seminfo_semvmx=32767
set shmsys:shminfo_shmmax=4294967295
set shmsys:shminfo_shmgni=100
```


- d. Enter a command similar to the following to reboot the system:

```
# /usr/sbin/reboot
```

- e. When the system restarts, log in and switch user to root.

9 Mount the Product Disc

The Oracle Database 10g software is available on both CD-ROM and DVD-ROM. These discs are in ISO 9660 format with Rockridge extensions.

On most Solaris systems, the product disc mounts automatically when you insert it into the drive. To verify that the disc is mounted correctly, follow these steps:

1. If necessary, enter a command similar to following to eject the currently mounted disc, then remove it from the drive:

```
# eject
```

2. Insert the disc into the CD-ROM or DVD-ROM drive.

3. To verify that the disc mounted automatically, enter a command similar to the following:

```
$ ls /cdrom/cdrom0
```

4. If this command fails to display the contents of the disc, enter a command similar to the following:

```
# /usr/sbin/mount -r -F hsfs /dev/dsk/cxytdzs2 /cdrom
```

In this example, `/cdrom` is the CD-ROM mount point directory and `/dev/dsk/cxytdzs2` is the device name for the CD-ROM device, for example `/dev/dsk/c0t6d0s2`.

10 Log In as the oracle User and Configure the oracle User's Environment

You run the Installer from the `oracle` account. However, before you start the Installer you must configure the environment of the `oracle` user. To configure the environment, you must:

- Set the default file mode creation mask (`umask`) to 022 in the shell startup file.
- Set the `DISPLAY`, `ORACLE_BASE`, and `ORACLE_SID` environment variables.

To set the `oracle` user's environment, follow these steps:

1. Start another terminal session.
2. Enter the following command to ensure that X Window applications can display on this system:

```
$ xhost +
```

3. Complete one of the following steps:

- If the terminal session is not connected to the system where you want to install the software, log in to that system as the `oracle` user.
- If the terminal session is connected to the system where you want to install the software, switch user to `oracle`:

```
$ su - oracle
```

4. To determine the default shell for the `oracle` user, enter the following command:

```
$ echo $SHELL
```

5. Open the `oracle` user's shell startup file in any text editor:
 - Bourne shell (`sh`), Bash shell (`bash`), or Korn shell (`ksh`):
`$ vi .profile`
 - C shell (`csh` or `tcsh`):
`% vi .login`
6. Enter or edit the following line in the shell startup file, specifying a value of `022` for the default file mode creation mask:
`umask 022`
7. Save the file and exit from the editor.
8. To run the shell startup script, enter the following command:
 - Bourne, Bash, or Korn shell:
`$. ./profile`
 - C shell:
`% source ./login`

9. If you determined that the `/tmp` directory had insufficient free disk space when checking the hardware requirements, enter the following commands to set the `TEMP` and `TMPDIR` environment variables. Specify a directory on a file system with sufficient free disk space.

- Bourne, Bash, or Korn shell:

```
$ TEMP=directory
$ TMPDIR=directory
$ export TEMP TMPDIR
```

- C shell:

```
% setenv TEMP directory
% setenv TMPDIR directory
```

10. If you are not installing the software on the local system, enter the following command to direct X applications to display on the local system:

- Bourne, Bash, or Korn shell:

```
$ DISPLAY=local_host:0.0 ; export DISPLAY
```

- C shell:

```
% setenv DISPLAY local_host:0.0
```

In this example, *local_host* is the host name or IP address of the system that you want to use to display the Installer (your workstation or PC).

11. Enter commands similar to the following to set the ORACLE_BASE and ORACLE_SID environment variables:

- Bourne, Bash, or Korn shell:

```
$ ORACLE_BASE=/u01/app/oracle  
$ ORACLE_SID=sales  
$ export ORACLE_BASE ORACLE_SID
```

- C shell:

```
% setenv ORACLE_BASE /u01/app/oracle  
% setenv ORACLE_SID sales
```

In these examples, */u01/app/oracle* is the Oracle base directory that you created earlier and *sales* is the name that you want to call the database (typically no more than five characters).

- 12.** Enter the following commands to ensure that the ORACLE_HOME and TNS_ADMIN environment variables are not set:

- Bourne, Bash, or Korn shell:

```
$ unset ORACLE_HOME
$ unset TNS_ADMIN
```

- C shell:

```
% unsetenv ORACLE_HOME
% unsetenv TNS_ADMIN
```

- 13.** To verify that the environment has been set correctly, enter the following commands:

```
$ umask
$ env | more
```

Verify that the `umask` command displays a value of `0022`, `022`, or `22` and the environment variables that you set in this section have the correct values.

11 Install Oracle Database 10g

After configuring the `oracle` user's environment, start the Installer and install the Oracle software, as follows:

Note: The following examples show paths to the `runInstaller` script on a CD-ROM. If you are installing the software from DVD-ROM, use a command similar to the following:

```
$ /mount_point/db/runInstaller
```

1. To start the Installer, enter the following commands:

- Automatically mounted CD-ROM:

```
$ cd /tmp  
$ /cdrom/cdrom0/runInstaller
```

- Manually mounted CD-ROM:

```
$ cd /tmp  
$ /cdrom/runInstaller
```


If the Installer does not appear, see the *Oracle Database Installation Guide for UNIX Systems* for information about how to troubleshoot X display problems.

2. Use the following guidelines to complete the installation:
 - The following table describes the recommended action for each Installer screen.

Note: If you have completed the tasks listed previously, you can complete the installation by choosing the default values on most screens.

- If you need more assistance, or if you want to choose an option that is not a default, click **Help** for additional information.
- If you encounter errors while installing or linking the software, see the *Oracle Database Installation Guide for UNIX Systems* for information about troubleshooting.

Screen	Recommended Action
Welcome	Click Next .
Specify Inventory Directory and Credentials	<p>Note: This screen appears only during the first installation of Oracle products on a system.</p> <p>Specify the following information, then click Next:</p> <p>Enter the full path of the inventory directory</p> <p>Verify that the path is similar to the following, where <i>oracle_base</i> is the value that you specified for the ORACLE_BASE environment variable:</p> <p><i>oracle_base</i>/oraInventory</p> <p>Specify operating system group name</p> <p>Verify that the group specified is the Oracle Inventory group:</p> <p>oinstall</p>
Run oraInstRoot.sh	<p>If prompted, run the following script in a separate terminal window as the <code>root</code> user:</p> <p><i>oracle_base</i>/oraInventory/oraInstRoot.sh</p>

Screen	Recommended Action
Specify File Locations	<p>In the Destination section, verify that the Path value for the Oracle home directory is similar to the following, then click Next:</p> <pre><i>oracle_base/product/10.1.0/db_1</i></pre>
Select Installation Type	<p>Select Enterprise Edition or Standard Edition, then click Next.</p>
Product-Specific Prerequisite Checks	<p>Verify that all of the prerequisite checks succeed, then click Next.</p> <p>The Installer checks the system to verify that it is configured correctly to run Oracle software. If you have completed all of the pre-installation steps in this guide, all of the checks should pass.</p> <p>In some circumstances, a check might fail even if you have completed all of the pre-installation steps. For example, you might have installed a later patch that obsoletes one of those listed in this guide.</p> <p>If a check fails, review the cause of the failure listed for that check on the screen. If possible, rectify the problem and rerun the check. Alternatively, if you are satisfied that your system meets the requirements, you can select the check-box for the failed check to manually verify the requirement.</p>

Screen	Recommended Action
Select Database Configuration	Accept the default choices, then click Next .
Specify Database Configuration Options	<p>Specify the following information, then click Next:</p> <p>Note: If you set the ORACLE_SID environment variable, its value is used as the default value for the global database name and SID.</p> <p>Global Database Name</p> <p>Specify a name for the database, followed by the domain name of the system:</p> <p><i>sales.your_domain.com</i></p> <p>The value that you specify, up to the first period, is also used for the SID value.</p> <p>Select Database Character Set</p> <p>Accept the default value, which is based on your system locale, or if you need to support more than one language, click Help for more information about the supported character sets.</p> <p>Create database with example schemas</p> <p>Choose this option to create the EXAMPLE tablespace that contains the Sample Schemas (optional, but recommended).</p>

Screen	Recommended Action
Select Database Management Option	Accept the default values, then click Next . Note: You can enable e-mail notifications after you have installed the software.
Specify Database File Storage Option	Select the File System option and specify the database file location, then click Next . Specify database file location: Specify the Oracle datafiles directory, if you created it: <code>/u02/oradata</code> Alternatively, accept the default location: <code>oracle_base/oradata</code>
Specify Backup and Recovery Options	Accept the default values, then click Next . Note: You can enable automated backups after you have installed the software.
Specify Database Schema Passwords	Enter and confirm passwords for all of the privileged database accounts, then click Next . Note: Oracle recommends that you specify a different password for each account. You must remember the passwords that you specify.
Summary	Review the information displayed, then click Install .

Screen	Recommended Action
Install	The Install screen displays status information while the product is being installed.
Configuration Assistants	<p>The Configuration Assistants screen displays status information for the configuration assistants that configure the software and create a database.</p> <p>After the Database Configuration Assistant finishes, click OK to continue.</p>
Setup Privileges	<p>When prompted, run the following script in a separate terminal window as the <code>root</code> user:</p> <pre><i>oracle_home</i>/root.sh</pre> <p>In this example, <i>oracle_home</i> is the directory where you installed the software. The correct path is displayed on the screen.</p> <p>Press Return to accept the default values for each prompt displayed by the script. When the script finishes, click OK.</p>

Screen	Recommended Action
End of Installation	<p>The configuration assistants configure several Web-based applications, including Oracle Enterprise Manager Database Control. This screen displays the URLs configured for these applications. Make a note of the URLs used.</p> <p>The port numbers used in these URLs are also recorded in the following file:</p> <p><code>oracle_home/install/portlist.ini</code></p> <p>To exit from the Installer, click Exit, then click Yes.</p>

12 Install Products from the Oracle Database 10g Companion CD

The Oracle Database 10g Companion CD contains products that improve the performance of or complement Oracle Database 10g. For most installations, Oracle recommends that you install Oracle Database 10g Products from the Companion CD.

Note: If you intend to use Oracle JVM or Oracle *interMedia*, you *must* install Oracle Database 10g Products from the Companion CD. This installation optimizes the performance of those products on your system.

Products Included on the Companion CD

The Companion CD includes two sets of products:

- **Oracle Database 10g Products**

Includes Oracle Database Examples, natively compiled Java libraries for Oracle JVM and Oracle *interMedia*, Oracle Text supplied knowledge bases

Note: You must install these products into the same Oracle home directory as Oracle Database 10g Release 1 (10.1.0).

- **Oracle Database 10g Companion Products**

Includes Oracle HTTP Server and Oracle HTML DB

Note: You must install Oracle HTTP Server into its own Oracle home directory. You must install Oracle HTML DB either with Oracle HTTP Server, or into an Oracle home directory that contains Oracle HTTP Server.

The following subsection describes how to install Oracle Database 10g Products. For more information about the products on the Companion CD, and for more detailed information about installing them, see the *Oracle Database Companion CD Installation Guide* which is located on the Companion CD.

Installing Oracle Database 10g Products

To install Oracle Database 10g Products, follow these steps:

1. As the `root` user, mount the Oracle Database 10g Companion CD CD-ROM or the Oracle Database 10g DVD-ROM.

For more information about mounting discs, see [Section 9, "Mount the Product Disc"](#) on page 25.

2. If necessary, log in as the Oracle software owner user that you used to install Oracle Database 10g (typically `oracle`).
3. Enter a command similar to the following to start the Installer:

- CD-ROM installation:

```
$ /mount_point/runInstaller
```

- DVD-ROM installation:

```
$ /mount_point/companion/runInstaller
```

The following table describes the recommended action for each Installer screen:

Screen	Recommended Action
Welcome	Click Next .
Specify File Locations	In the Destination section, select the Name or Path value that specifies the Oracle home directory where you installed Oracle Database 10g, then click Next . The default Oracle home path is similar to the following: <i>oracle_base/product/10.1.0/db_1</i>
Select a Product to Install	Select Oracle Database 10g Products , then click Next .
Summary	Review the information displayed, then click Install .

Screen	Recommended Action
Install	The Install screen displays status information while the product is being installed.
End of Installation	To exit from the Installer, click Exit , then click Yes .

13 What to Do Next

To become familiar with this release of Oracle Database, Oracle suggests that you complete the following tasks:

- Log in to Oracle Enterprise Manager Database Control using a Web browser.

Oracle Enterprise Manager Database Control is a Web-based application that you can use to manage a single Oracle database. The default URL for Database Control is:

`http://host.domain:5500/em/`

To log in, use the user name SYS and connect as SYSDBA. Use the password that you specified for this user during the Oracle Database 10g installation.

- See Chapter 4 of the *Oracle Database Installation Guide for UNIX Systems* for information about required and optional

post-installation tasks, depending on the products that you want to use.

- Review Chapter 5 in the *Oracle Database Installation Guide for UNIX Systems* for information about how to use Database Control to learn about the configuration of your installed database.
- Read the *Oracle Database 2 Day DBA* guide, to learn more about using Oracle Enterprise Manager Database Control to administer a database.

This guide, designed for new Oracle DBAs, describes how to use Database Control to manage all aspects of an Oracle database installation. It also provides information about how to enable e-mail notifications and automated backups, which you might not have configured during the installation.

14 Additional Information

This section contains information about the following:

- [Product Licenses](#)
- [Purchasing Licenses, Version Updates, and Documentation](#)
- [Contacting Oracle Support Services](#)
- [Locating Product Documentation](#)

Product Licenses

You are welcome to install and evaluate the products included in this media pack for 30 days under the terms of the Trial License Agreement. However, you must purchase a program license if you want to continue using any product after the 30 day evaluation period. See the following section for information about purchasing program licenses.

Purchasing Licenses, Version Updates, and Documentation

You can purchase program licenses, updated versions of Oracle products, and printed versions of Oracle documentation from the Oracle Store Web site:

<http://oraclestore.oracle.com/>

Contacting Oracle Support Services

If you have purchased Oracle Product Support, you can call Oracle Support Services for assistance 24 hours a day, seven days a week. For information about purchasing Oracle Product Support or contacting Oracle Support Services, go to the Oracle Support Services Web site:

<http://www.oracle.com/support/>

Locating Product Documentation

Documentation for Oracle products is available in both HTML and Adobe portable document format (PDF) formats from several locations:

- On discs in the media pack:
 - Platform-specific documentation is available on the product discs. To access the documentation, see the `welcome.htm` file located in the top-level directory of the CD-ROM or DVD-ROM.
 - Generic product documentation is available on the Oracle Documentation Library CD-ROM and on the DVD-ROM.

- From the Oracle Technology Network Web site:

<http://otn.oracle.com/documentation/>

To view PDF documents, download the free Adobe Acrobat Reader from the Adobe Web site, if necessary:

<http://www.adobe.com/>

